



NOTES:

1. TANK CAR ILLUSTRATED ON THIS DRAWING CONFORMS TO APPLICABLE REQUIREMENTS OF THE US DEPT OF TRANSPORTATION AND THE AAR.
2. ALL SAFETY APPLIANCES SECURED BY 1/2 IN. MIN TWO PIECE RIVETS AND OR BOLTS W/BOLT ENDS RIVETED OVER NUTS, EXCEPT PLATFORM AND END BOARD GRATING ATTACHMENT BOLTS WHICH MAY BE CHISEL CHECKED IN LIEU OF RIVETING OVER.
3. MIN CURVE CHARACTERISTICS:
 - A. ON CURVE AND UNCOUPLED----- 98 FT RAD (9° TRUCK SWING)
 - B. COUPLED TO LIKE CAR,----- 150 FT RAD ONE ON CURVE AND ONE ON TANGENT.
 - C. COUPLED TO AAR 40 FT 0 IN. BASE----- 150 FT RAD CAR WITH TANK CAR ON CURVE AND BASE CAR ON TANGENT.
4. SEE APPLICATION DRAWING-CARD HOLDER, FOR AEI TAG, DEFECT CARD HOLDER, ROUTE CARD HOLDER, AND PLACARD HOLDER.
5. TANK CAR IS 13,170 GAL, DOT 114S340W.

PART NO.: 5U786500

AAR APPLN NO. 951007
20
18-12404

JCC 04-26-95
RVD 05-01-95

TBB 05-02-95

GENERAL
ARRANGEMENT

5-U-7865
1/32